


# □ LUCID CEILING



## INSTALLATION

Ceiling version

## CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block  
Luminaires for dimming are delivered with 5-pole terminal block

## MATERIAL

The body of the luminaire is extruded aluminium,  
eloxed finish

## LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

## DIFFUSER

PMMA OPAL

## LIGHT DISTRIBUTION

Direct and sidewalls

## EMERGENCY LIGHTING

A unit with integrated emergency is an option

## DIMMING

Most models can be delivered with ballast  
for dimming (TOUCHDIM, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SLC130	585x57x70	8	1500/1580
SLC250	585x57x70	14	2340/2450
SLC195	860x57x70	13	2250/2370
SLC375	860x57x70	21	3510/3690
SLC260	1145x57x70	16	3000/3160
SLC500	1145x57x70	28	4680/4900
SLC325	1425x57x70	21	3750/3950
SLC625	1425x57x70	35	5850/6150
SLC2x195	1710x57x70	26	4500/4740
SLC2x375	1710x57x70	42	700/7380
SLC2x230	1990x57x70	29	5250/5530
SLC2x440	1990x57x70	49	8190/8610
SLC2x260	2280x57x70	32	6000/6320
SLC2x500	2280x57x70	56	9360/9800
SLC2x325	2840x57x70	42	7500/7900
SLC2x625	2840x57x70	70	11700/12300

#### COLOR TEMPERATURE

3000K /3K  
4000K /4K

#### OPTIC

PMMA OPAL /--

#### DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI  
WIRELESS /WRS

#### COLORS

ELOX /...

#### ACCESSORIES

