


□ LUCID SUSPENDED



ARCHILIGHT



INSTALLATION

Suspended version

CONNECTION

Non dimmable luminaires are delivered with 3-pole terminal block
Luminaires for dimming are delivered with 5-pole terminal block

MATERIAL

The body of the luminaire is extruded aluminium, eloxed or powder coated finish

LIGHT SOURCE

LED Tridonic or TCI, min. 150Lm/W, 3000K or 4000K

DIFFUSER

PMMA OPAL

LIGHT DISTRIBUTION

Direct and sidewalls

EMERGENCY LIGHTING

A unit with integrated emergency is an option

DIMMING

Most models can be delivered with ballast for dimming (TOUCHDIM, DALI)



DIRECT CODE	(mm)	W	Lm from 3000K/4000K
SLS130	585x57x70	8	1500/1580
SLS250	585x57x70	14	2340/2450
SLS195	860x57x70	13	2250/2370
SLS375	860x57x70	21	3510/3690
SLS260	1145x57x70	16	3000/3160
SLS500	1145x57x70	28	4680/4900
SLS325	1425x57x70	21	3750/3950
SLS625	1425x57x70	35	5850/6150
SLS2x195	1710x57x70	26	4500/4740
SLS2x375	1710x57x70	42	700/7380
SLS2x230	1990x57x70	29	5250/5530
SLS2x440	1990x57x70	49	8190/8610
SLS2x260	2280x57x70	32	6000/6320
SLS2x500	2280x57x70	56	9360/9800
SLS2x325	2840x57x70	42	7500/7900
SLS2x625	2840x57x70	70	11700/12300

Delivered incl. 2 m self-locking suspensions

COLOR TEMPERATURE

3000K /3K
4000K /4K

OPTIC

PMMA OPAL /--

DIMMABLE OPTIONS

DALI, TOUCHDIM /DALI
WIRELESS /WRS

COLORS

ELOX /...

ACCESSORIES

57
70
SL PKK
END CAP
2PCS

75
75
SPPKBO3075 (3X0,75)
SPPKBO5075 (5X0,75)
TRANSPARENT CABLE 2 METRES
WITH CEILING BOX

25

